

DAILY

IVECO

Model	35S12V8	35S12V10	35S15V12	50C15V8	50C15V12	50C15V15	50C15V17	50C15 Cab	65C15CC	65C15 Crew Cab	
Dimensions (mm)											
Wheelbase	3 000	3 000	3 300	3 000	3 300	3 950	3 950	3 750	4 350	4 350	
Overall length	5 477	5 477	5 997	5 477	5 997	7 012	7 012	6 538	7 340	7 340	
Front overhang	998	998	998	998	998	998	998	998	998	998	
Rear overhang	1 479	1 479	1 479	1 479	1 699	2 064	2 064	1 665	1 890	1 890	
Overall width	1 996	1 996	1 996	1 996	1 996	1 996	1 996	2 200	2 060	2 060	
Overall height (unladen)	2 270	2 645	2 640	2 270	2 745	2 745	2 930	2 275	2 325	2 320	
Cargo Area											
Capacity (m ³)	8.3	10.2	12	8.3	12	15.6	17.2	N/A	N/A	N/A	
Internal length (mm)	3 000	3 000	3 520	3 021	3 520	4 560	4 560	N/A	N/A	N/A	
Internal width (mm)	1 800	1 800	1 800	1 800	1 800	1 800	1 800	N/A	N/A	N/A	
Internal height (mm)	1 545	1 900	1 900	1 545	1 900	1 900	2 100	N/A	N/A	N/A	
Gross Ratings (kg)											
GVM	3 600	3 600	3 600	5 400	5 400	5 400	5 400	5 400	6 500	6 500	
GCM	5 600	5 600	5 600	8 700	8 700	8 700	8 700	8 700	10 000	10 000	
Maximum payload	1 600	1 520	1 445	2 965	2 935	2 830	2 790	3 370	4 210 (including body)	4 100 (including body)	
Engines											
Cylinders	Four (16 valves)										
Emission compliance	Common Rail Generation 2										
Power (kW)	85 at 3 200 to 3 900 r/min		107 at 3 000 to 3 500 r/min			130 at 3 200 to 3 500 r/min		107 at 3 000 to 3 500 r/min		130 at 3 200 to 3 500 r/min	
Torque (Nm)	270		350 at 1 400 to 2 600 r/min			400 at 1 250 to 3 000 r/min		350 at 1 400 to 2 600 r/min		400 at 1 250 to 3 000 r/min	
Gearboxes											
Type	5S300OD five-speed Synchronesh		6S400OD six-speed Synchronesh								
Suspension											
Front	Transverse leaf			Independent with torsion bars							
Rear	Single acting parabolic leaf spring			Parabolic leaf spring							
Brakes											
Front	Diameter ventilated disc brakes / 290 mm								Diameter ventilated disc brakes / 301 mm		
Rear	Diameter disc brakes / 289 mm			Diameter disc brakes / 290 mm				Diameter disc brakes / 306 mm			
ABS & EBD Standard											

